



IDPT 100

Differential Pressure Transmitter for Process Industry

accuracy according to IEC 60770:
0.1 % FSO

Differential pressure

from 10 mbar up to 20 bar

Static pressure

max. 400 bar

Output signal

2-wire: 4 ... 20 mA

RS485 with Modbus RTU protocol

Special characteristics

- ▶ compact design
- ▶ fast response time
- ▶ aluminium die cast case
- ▶ zero adjustment via button

Optional versions




- ▶ several process connections

The differential pressure transmitter IDPT 100 has been especially designed for fast test processes in leakage and flow measurement, where a fast response time and high sampling rate are necessary.

The compact design of the IDPT 100 facilitates the usage in standardised applications. For instance, the installation in 19" racks.

The IDPT 100 with optionally RS485 interface uses the communication protocol Modbus RTU which has found the way in industrial communication as an open protocol. The Modbus protocol is based on a master Slave architecture with which up to 247 Slaves can be questioned by a master – the data will transfer in binary form.

The typical areas of use are

-  Machine and plant engineering
-  Environmental technology
-  Energy production



Modbus®

| Differential pressure ranges | | | | | | | |
|--|--|------------------------------|---|--------------------------------|-----------------------|--------------------|--|
| Pressure range P _N diff. | 10 mbar | 60 mbar | 100 mbar | 400 mbar | 2.5 bar | 20 bar | |
| Pressure range P _N symmetric (diff.) | ± 10 mbar | ± 60 mbar | ± 100 mbar | ± 400 mbar | on request | on request | |
| Permissible static pressure | 70 bar | 400 bar | 400 bar | 400 bar | 400 bar | 400 bar | |
| Output signal / Supply | | | | | | | |
| Standard | 2 wire : 4 ... 20 mA / V _S = 12 ... 32 V _{DC} | | | | | | |
| Option | digital: RS 485 with Modbus RTU protocol / V _S = 9 ... 32 V _{DC} (delay time: 500 msec) | | | | | | |
| Performance | | | | | | | |
| Accuracy ¹ | P _N ≥ 60 mbar: ≤ ± 0.1 % FSO P _N < 60 mbar: ≤ ± 0.2 % FSO | | | | | | |
| Permissible load | R _{max} = [(V _S - V _{S min}) / 0.02 A] Ω | | | | | | |
| Influence supply | supply: 0.05 % FSO / 10 V load: 0.05 % FSO / kΩ | | | | | | |
| Influence static pressure P _N [Pa/100 bar] | 10 mbar 18 | 60 mbar 30 | 400 mbar 40 | 2.5 bar 250 | 20 bar 2000 | | |
| Influence installation position | max. 400 Pa (can be compensated by zero-point correction) for ranges < 60 mbar please state installation position on the order | | | | | | |
| Long term stability | P _N ≥ 60 mbar: ≤ ± 0.05 %FSO/ year at reference conditions P _N < 60 mbar: ≤ ± 0.15 %FSO/ year at reference conditions | | | | | | |
| Sampling rate | 250 Hz | | | | | | |
| Turn-on time | approx. 260 msec | | | | | | |
| Response time (10 ... 90 %) | 10 msec | | | | | | |
| ¹ accuracy according to IEC 60770 – limit point adjustment (non-linearity, hysteresis, repeatability) | | | | | | | |
| Thermal effects (Offset and Span) | | | | | | | |
| Thermal error (offset and span) | ≤ ± 0.1 % FSO / 10 K | | | | | | |
| Compensated range | -20 ... 80 °C | | | | | | |
| Permissible temperatures | medium: -25 ... 85°C | | electronics / environment: -25 ... 85°C | | storage: -25 ... 85°C | | |
| Electrical protection | | | | | | | |
| Short-circuit protection | permanent | | | | | | |
| Reverse polarity protection | no damage, but also no function | | | | | | |
| Electromagnetic compatibility | emission and immunity according to EN 61326 | | | | | | |
| Mechanical stability | | | | | | | |
| One-sided overload | according to the maximum static pressure of differential pressure sensor | | | | | | |
| Vibration | 5 g RMS (25 ... 2000 Hz) | | | according to DIN EN 60068-2-6 | | | |
| Shock | 100 g / 1 msec | | | according to DIN EN 60068-2-27 | | | |
| Materials | | | | | | | |
| Pressure port / flange | standard | stainless steel 304 / 1.4301 | | | | others: on request | |
| | option | stainless steel 316 / 1.4401 | | | | | |
| Diaphragm | stainless steel 316L / 1.4404 | | | | others: on request | | |
| Vent and dump valves | | | | | | | |
| Blanking plugs | standard | stainless steel 304 / 1.4301 | | | | others: on request | |
| | option | stainless steel 316 / 1.4401 | | | | | |
| Bolts and nuts | standard | stainless steel 304 / 1.4301 | | | | others: on request | |
| | option | stainless steel 316 / 1.4401 | | | | | |
| Housing | aluminium die cast with epoxy painting (grey) | | | | others: on request | | |
| Cable gland | polyamide | | | | | | |
| Seals (media wetted) | standard | FKM | | | | others: on request | |
| | option | EPDM, NBR | | | | | |
| Filling fluids | silicone oil | | | | others: on request | | |
| Media wetted parts | pressure port, seal of pressure port, diaphragm | | | | | | |

IDPT 100

Differential Pressure Transmitter

Technical Data

| Miscellaneous | | |
|--|---|-----------------------|
| Mounting bracket (optionally) | material C-steel or stainless steel 304 / 1.4401 weight 0.45 kg (incl. bolts and nuts) | |
| Ingress protection | IP 66 / IP 67 | |
| Installation position | any ² | |
| Weight | approx. 1800 g | |
| Current consumption | approx. 23 mA | |
| Operational life | 100 million load cycles | |
| CE-conformity | EMC Directive: 2014/30/EU Pressure Equipment Directive: 2014/68/EU (module A) ³ | |
| ² Pressure transmitters are calibrated in a vertical position with the pressure connection down. If this position is changed on installation there can be slight deviations in the zero point. Press the button for zero adjustment (see operating manual). | | |
| ³ This directive is only valid for devices with maximum permissible overpressure > 200 bar. | | |
| Connections | | |
| Electrical connection | terminal clamps in clamping chamber (for cable-Ø max.2.5 mm ²) | |
| Process connections | internal thread 1/4" - 18 NPT / fixing 7/16 UNF internal thread 1/4" - 18 NPT / fixing M10 others: on request | |
| Standard option | | |
| Wiring diagram | | |
| <div style="display: flex; justify-content: space-around;"> <div style="text-align: center;"> <p>2-wire-system (current)</p> </div> <div style="text-align: center;"> <p>RS485 / Modbus RTU</p> </div> </div> | | |
| Pin configuration | | |
| Electrical connection | terminal clamps | M12x1 / metal (4-pin) |
| Supply + | + Ub | 1 |
| Supply - | - Ub | 3 |
| for RS485 / Modbus RTU: | | |
| A (+) | A | 2 |
| B (-) | B | 4 |
| Ground | | plug housing |
| Dimensions (mm / in) | | |
| | | |

Ordering code IDPT 100

IDPT 100



| | | | | | | | | | | | | | | | | | | |
|---|--|---|---|---|---|--|--|--|---|---|---|--|--|--|--|--|--|---------|
| Pressure | | | | | | | | | | | | | | | | | | |
| | differential pressure | 3 | 4 | 5 | | | | | | | | | | | | | | |
| Input | | | | | | | | | | | | | | | | | | |
| | 10 mbar | 0 | 1 | 0 | 0 | | | | | | | | | | | | | |
| | 60 mbar | 0 | 6 | 0 | 0 | | | | | | | | | | | | | |
| | 100 mbar | 1 | 0 | 0 | 0 | | | | | | | | | | | | | |
| | 400 mbar | 4 | 0 | 0 | 0 | | | | | | | | | | | | | |
| | 2.5 bar | 2 | 5 | 0 | 1 | | | | | | | | | | | | | |
| | 20 bar | 2 | 0 | 0 | 2 | | | | | | | | | | | | | |
| | -10 ... 10 mbar | S | 0 | 1 | 0 | | | | | | | | | | | | | |
| | -60 ... 60 mbar | S | 0 | 6 | 0 | | | | | | | | | | | | | |
| | -100 ... 100 mbar | S | 1 | 0 | 0 | | | | | | | | | | | | | |
| | -400 ... 400 mbar | S | 4 | 0 | 0 | | | | | | | | | | | | | |
| | customer | 9 | 9 | 9 | 9 | | | | | | | | | | | | | consult |
| Output | | | | | | | | | | | | | | | | | | |
| | 4 ... 20 mA / 2-wire | | | | | | | | 1 | | | | | | | | | |
| | RS485 Modbus RTU | | | | | | | | L | 5 | | | | | | | | |
| | customer | | | | | | | | 9 | | | | | | | | | consult |
| Accuracy | | | | | | | | | | | | | | | | | | |
| P _N ≥ 60 mbar: | 0.1 % FSO | | | | | | | | 1 | | | | | | | | | |
| P _N < 60 mbar: | 0.2 % FSO | | | | | | | | B | | | | | | | | | |
| | customer | | | | | | | | 9 | | | | | | | | | consult |
| Housing | | | | | | | | | | | | | | | | | | |
| | aluminium | | | | | | | | L | | | | | | | | | |
| | customer | | | | | | | | 9 | | | | | | | | | consult |
| Electrical connection | | | | | | | | | | | | | | | | | | |
| | terminals / cable gland M12x1.5 | | | | | | | | A | K | 2 | | | | | | | |
| | male plug M12x1 (4-pin) / metal | | | | | | | | M | 1 | 7 | | | | | | | |
| | customer | | | | | | | | 9 | 9 | 9 | | | | | | | consult |
| Process connection | | | | | | | | | | | | | | | | | | |
| | 1/4" - 18 NPT F / fixing 7/16 UNF | | | | | | | | N | 2 | 0 | | | | | | | |
| | 1/4" - 18 NPT (F / vertical) / fixing 7/16 UNF | | | | | | | | N | 2 | 1 | | | | | | | |
| | 1/4" - 18 NPT F / fixing M10 | | | | | | | | N | 3 | 0 | | | | | | | |
| | 1/4" - 18 NPT (F / vertical) / fixing M10 | | | | | | | | N | 3 | 1 | | | | | | | |
| | customer | | | | | | | | 9 | 9 | 9 | | | | | | | consult |
| Valve | | | | | | | | | | | | | | | | | | |
| | without | | | | | | | | 0 | | | | | | | | | |
| | with vent | | | | | | | | 1 | | | | | | | | | |
| | with vent (top) | | | | | | | | 2 | | | | | | | | | |
| | with vent (bottom) | | | | | | | | 3 | | | | | | | | | |
| Material flange, valves, screws, ... | | | | | | | | | | | | | | | | | | |
| | stainless steel 1.4301 (304 SS) | | | | | | | | 0 | 2 | | | | | | | | |
| | stainless steel 1.4401 (316 SS) | | | | | | | | 1 | 2 | | | | | | | | |
| | customer | | | | | | | | 9 | 9 | | | | | | | | consult |
| Diaphragm / filling fluid | | | | | | | | | | | | | | | | | | |
| | stainless steel 1.4435 (316L) / silicone oil | | | | | | | | 1 | 1 | | | | | | | | |
| | customer | | | | | | | | 9 | 9 | | | | | | | | consult |
| Seal | | | | | | | | | | | | | | | | | | |
| | FKM | | | | | | | | 1 | | | | | | | | | |
| | EPDM | | | | | | | | 3 | | | | | | | | | |
| | NBR | | | | | | | | 5 | | | | | | | | | |
| | PTFE | | | | | | | | 4 | | | | | | | | | |
| | customer | | | | | | | | 9 | | | | | | | | | consult |
| Special version | | | | | | | | | | | | | | | | | | |
| | standard | | | | | | | | 0 | 0 | 0 | | | | | | | |
| | customer | | | | | | | | 9 | 9 | 9 | | | | | | | consult |